

110 TLB Attachment Compatibility Chart

Rev. 1-Sep-2006

| Attachment | Compatibility | | | Mounting Location | | | Availability | |
|-------------------------------|---------------------------------------|---|---------------------------|-------------------------|--------------------------|--------------------------------|--------------|-----|
| | Approved and Recommended ¹ | Approved but Not Recommended ² | Not Approved ³ | Loader ^{4, 11} | Backhoe ^{5, 12} | 3-Point Hitch ^{6, 13} | C&CE | CWP |
| Augers | | | | | | | | |
| PA15 | | | √ | | | | | |
| PA30 | √ | | | | √ | | √ | √ |
| CA15 | | | √ | | | | | |
| CA25 | √ | | | | √ | | | √ |
| Buckets, Backhoe | | | | | | | | |
| 9 in. | | | √ | | | | | |
| 12 in. | √ | | | | √ | | √ | √ |
| 16 in. | √ | | | | √ | | √ | √ |
| 18 in. | √ | | | | √ | | √ | √ |
| 20 in. | √ | | | | √ | | √ | √ |
| 24 in. | √ | | | | √ | | √ | √ |
| 30 in. | √ | | | | √ | | √ | √ |
| 34 in. | | √ | | | √ | | | √ |
| 36 in. | √ | | | | √ | | √ | √ |
| Backhoes | | | | | | | | |
| BH8 | | | √ | | | | | |
| BH9 | | | √ | | | | | |
| BH11 | | | √ | | | | | |
| Bale Spear | √ | | | √ | | | √ | √ |
| Breakers | | | | | | | | |
| HB15-II | | | √ | | | | | |
| HB30-II | | | √ | | | | | |
| HB50-II | √ | | | | √ | | √ | √ |
| HB75-II | | | √ | | | | | |
| HB100-II | | | √ | | | | | |
| Brooms, Angle / Pickup | | | | | | | | |
| BA72 | | | √ | | | | | |
| BA84 | | | √ | | | | | |
| BP72 | | | √ | | | | | |
| BR72 | | √ ¹¹ | | √ | | | | √ |
| BP84 | | | √ | | | | | |
| BR84 | | | √ | | | | | |
| Buckets, Loader | | | | | | | | |
| Construction 60 in. | | √ ⁸ | | √ | | | | √ |
| 66 in. | | √ ⁸ | | √ | | | √ | √ |

| | | | | | | | | |
|---|------|--------|---|---|--|--|---|---|
| 72 in. | √ | | | √ | | | √ | √ |
| 78 in. (HD) | | | √ | | | | | |
| 84 in. (HD) | | | √ | | | | | |
| Foundry 66 in. | | √ 8 | | √ | | | √ | √ |
| 72 in. | √ | | | √ | | | √ | √ |
| 78 in. (HD) | | | √ | | | | | |
| Manure / Slurry 72 in. | √ | | | √ | | | | √ |
| 84 in. | | | √ | | | | | |
| Multi-Purpose (4-in-1) 66 in. | | √ 8 | | √ | | | | √ |
| 72 in. | √ | | | √ | | | √ | √ |
| 78 in. | | | √ | | | | | |
| 84 in. | | | √ | | | | | |
| Tooth 60 in. | | √ 8 | | √ | | | | √ |
| 66 in. | | √ 8 | | √ | | | | √ |
| 72 in. | √ | | | √ | | | | √ |
| 78 in. (HD) | | | √ | | | | | |
| 84 in. (HD) | | | √ | | | | | |
| Utility 66 in. | | √ 8 | | √ | | | √ | √ |
| 72 in. | √ | | | √ | | | √ | √ |
| 78 in. (HD) | √ 10 | | | √ | | | | √ |
| 84 in. (HD) | √ 10 | | | √ | | | √ | √ |
| Cold Planers | | | | | | | | |
| CP12B | | | √ | | | | | |
| CP16 | | | √ | | | | | |
| CP18 | | | √ | | | | | |
| CP24 | | | √ | | | | | |
| Grapples | | | | | | | | |
| Brush Tined GT72 | | √ 7 | | √ | | | √ | √ |
| GT80 | | | √ | | | | | |
| Scrap GS66 | | √ 7, 8 | | √ | | | √ | √ |
| GS72 | | √ 7 | | √ | | | √ | √ |
| GS78 | | | √ | | | | | |
| GS84 | | | √ | | | | | |
| Utility Ag GU66 | | √ 8 | | √ | | | √ | √ |
| GU72 | √ | | | √ | | | √ | √ |
| GU78 | | | √ | | | | | |

| | | | | | | | | |
|--|---------------------------|------|-------------|---|---|---|---|---|
| Landplanes | | | | | | | | |
| LP72 | | | √ | | | | | |
| LP78 | | | √ | | | | | |
| LP84 | | | √ | | | | | |
| Pallet Forks | | | | | | | | |
| Pin | √ | | | √ | | | | √ |
| Rail | √ | | | √ | | | √ | √ |
| Heavy-Duty | | | √ | | | | | |
| Power Rakes | | | | | | | | |
| PR72B | | | √ | | | | | |
| PR84B | | | √ | | | | | |
| PR96B | | | √ | | | | | |
| Roller Levels | | | | | | | | |
| RL66 | | | √ | | | | | |
| RL84 | | | √ | | | | | |
| Rotary Tillers | | | | | | | | |
| RT55 | | √ 11 | | √ | | | | √ |
| RT73 | | √ 11 | | √ | | | | √ |
| Snow / Utility Blades | | | | | | | | |
| BL7 | | | √ 9 | | | | | |
| BL8 | | | √ 9 | | | | | |
| BL9 | | | √ 9 | | | | | |
| BL10 | | | √ 9 | | | | | |
| Three-Point Hitch | Rear | | SSL Adapter | | | √ | √ | |
| Thumb, Hydraulic (clamp) | | | | | | | | |
| 22 in. | √ | | | | √ | | √ | √ |
| Trenchers | | | | | | | | |
| TR36B | | | √ | | | | | |
| TR48B | | | √ | | | | | |
| TR60B | | | √ | | | | | |
| Vibratory Rollers | | | | | | | | |
| VR66B | | √ 11 | | √ | | | | √ |
| VR66 Sheep's Foot | | √ 11 | | √ | | | | √ |
| VR73B | | √ 11 | | √ | | | | √ |
| VR73 Sheep's Foot | | √ 11 | | √ | | | | √ |
| VR84B | | | √ | | | | | |
| John Deere and Frontier ASAE Category I Three-Point Hitch Attachments | Refer to Notes 13 and 14. | | | | | √ | √ | |
| Box Blade BB1284 (Frontier) | √ 14 | | | | | √ | √ | |

| | | | | | | | | |
|------------------------|------|--|--|--|--|---|---|--|
| Ballast Box BW14701 | √ 14 | | | | | √ | √ | |
| BW13661 | √ 14 | | | | | √ | √ | |

Notes:

1. "Approved and Recommended" means that the attachment will fit the 110 TLB and the performance will be optimum.
2. "Approved but Not Recommended" means that the attachment will fit the 110 TLB but the performance will not be optimum due to hydraulic system limitations (flow or lift capacity).
3. "Not Approved" means that the attachment may or may not fit the 110 TLB but the combination may cause machine damage or instability.
4. The 110 TLB uses Skid Steer Loader (SSL) style attaching plates on the loader. However, SSL attachments not shown in this chart are not approved for use on the 110 TLB.
5. The backhoe on the 110 TLB is compatible with pin on attachments (standard) and quick change attachments used on mini-excavators (requires the optional Mechanical Quick Coupler Interface adapter). However, Mini-excavator attachments not shown in this chart are not approved for use on the 110 TLB.
6. The 110 TLB comes standard with a 540 RPM power take off (PTO). The ASAE Category I Three-Point Hitch is optional.
7. The weight of this attachment may significantly limit net lift capacity.
8. The width of this attachment is undersized for the 110 TLB. Performance may be significantly limited.
9. This attachment can create side loads that may potentially damage the loader structure.
10. Intended for light materials only.
11. Optional auxiliary hydraulic flow to the loader is 12.2 GPM at rated speed and may not be sufficient for some hydraulically-powered attachments.
12. Optional auxiliary hydraulic flow to the backhoe is 16.3 GPM at rated speed and may not be sufficient for some hydraulically-powered attachments.
13. Optional auxiliary hydraulic flow to the tractor-mounted rear remotes is 12.2 GPM at rated speed and may not be sufficient for some hydraulically-powered attachments.
14. The optional ASAE Category I Three-Point Hitch makes the 110 TLB compatible with a wide array of John Deere and Frontier Three-Point Hitch attachments. However, due to stability issues, only the listed John Deere ballast boxes (with 1250 lbs ballast) and the Frontier box blade are approved for use with the front loader when the backhoe is removed. When selecting PTO-powered attachments note that the 110 TLB comes standard with a 540 RPM Power Take Off (PTO), rated at 33 horsepower.