

**BAD BOY**  
**TRACTORS**

**40** **SERIES**



**MID-SIZED TRACTORS FEATURING OVER-SIZED PERFORMANCE.**







# 40 SERIES



TRACTOR MODEL	4025	4035	4035 CAB
TYPE	3 CYLINDER, WATER COOLED, DIESEL	3 CYLINDER, WATER COOLED, DIESEL	3 CYLINDER, WATER COOLED, DIESEL
ENGINE HP @ RPM (KW)	24 (18)	35 (26.2)	35 (26.2)
DISPLACEMENT (IN) (KW)	104.5 (1,714)	104.5 (1,714)	104.5 (1,714)
NUMBER OF CYLINDERS	3	3	3
FUEL TANK (GAL) (L)	7.1 (27)	7.1 (27)	7.1 (27)
<b>DRIVE TRAIN</b>			
TRANSMISSION	HST	HST	HST
NUMBER OF SPEEDS	2 RANGE	2 RANGE	2 RANGE
CLUTCH	NO	NO	NO
BRAKES	WET, MULTI-DISC	WET, MULTI-DISC	WET, MULTI-DISC
<b>PTO</b>			
TYPE	INDEPENDENT	INDEPENDENT	INDEPENDENT
REAR(MID) PTO SPEED	540	540	540
PTO HP (KW)	21(15.7)	30 (22.5)	30 (22.5)
<b>HYDRAULICS</b>			
TYPE	HYDROSTATIC POWER STEERING	HYDROSTATIC POWER STEERING	HYDROSTATIC POWER STEERING
TOTAL HYDRAULIC FLOW (POWER STEERING+IMPLEMENT)	11.5 (4+7.5)	12.6 (4.4+8.2)	12.6 (4.4+8.2)
3-POINT HITCH	CAT I	CAT I	CAT I
REAR REMOTE VALVE	OPTIONAL (UP TO 2)	OPTIONAL (UP TO 2)	OPTIONAL (UP TO 2)
3POINT HITCH LIFT CAPACITY @24" BEHIND LIFT POINT	2,425 (1,100)	2,425 (1,100)	2,425 (1,100)
<b>ELECTRICAL</b>			
BATTERY	12 V, 540 CCA	12 V, 540 CCA	12 V, 540 CCA
ALTERNATOR	12 V, 50 A	12 V, 50 A	12 V, 50 A
<b>DIMENSIONS</b>			
OVERALL LENGTH IN(MM)	120.9 (3,071)	120.9 (3,071)	120.9 (3,071)
OVERALL WIDTH IN(MM)	56.3 (1,430)	56.3 (1,430)	55.6 (1,413)
OVERALL HEIGHT IN(MM)	97.3 (2,471)	97.3 (2,471)	89.3 (2,267)
WHEELBASE IN(MM)	65.7 (1,670)	65.7 (1,670)	65.7 (1,670)
MINIMUM GROUND CLEARANCE IN(MM)	14.4 (366)	14.4 (366)	13.1 (334)
TURNING RADIUS	45°	45°	45°
WEIGHT LBS(KG)	2,969 (1,347)	3,163 (1,435)	3,547(1,609)
<b>WHEELS &amp; TIRES</b>			
IND (FRONT)	28X8.50-15	28X8.50-15	28X8.5-14
IND (REAR)	43X16.00-20	43X16.00-20	15-19.5
<b>LOADER MODEL</b>			
<b>BBL400</b>		<b>BBL400</b>	<b>BBL400C</b>
STANDARD BUCKET SIZE (IN)	62"	62"	62"
MAXIMUM LIFT HEIGHT (IN)	104"	104"	104"
DIG DEPTH (IN)	1.8"	1.8"	1.8"
LIFT CAPACITY TO FULL HEIGHT AT PIVOT PIN (LBS)	2200	2200	2200
BREAKOUT FORCE (LBS)	3660	3660	3660
SHIPPING WEIGHT (LBS)	1007	1007	1007
<b>BACKHOE MODEL</b>			
<b>BBH400</b>		<b>BBH400</b>	<b>BBH400</b>
STANDARD BUCKET SIZE (IN)	16"	16"	16"
TYPE	SUBFRAME-MOUNTED, QUICK ATTACH	SUBFRAME-MOUNTED, QUICK ATTACH	SUBFRAME-MOUNTED, QUICK ATTACH
MAXIMUM DIG DEPTH (IN)	92.2"	92.2"	92.2"
DIG FORCE BUCKET (LBS)	4380	4380	4380
SHIPPING WEIGHT (LBS)	1270	1270	1270