

LUBRICATION TABLE

Application	Kind of Oil	API Classification	Air Temperature	Grade (SAE NO.)		Description
				Single	Multi	
Engine	Motor Oil	CC CD	Below -10°C (14°F)	5W	5W-20	Use good grade oil of famous brand.
			-20 ~ 0°C (-4 ~ 32°F)	10W	10W-30	
			-10 ~ 10°C (14 ~ 50°F)	20W		
			0 ~ 20°C (32 ~ 68°F)	20		
			10 ~ 35°C (50 ~ 95°F)	30		
			30°C (86°F) & above	40	20W-40	
Transmission/ Hydraulic, 4WD Front Axle.	Gear Oil * Farm tractor use transmission/hydraulic oil or multi-service fluid.	GL-3 or better	Below 0°C (32°F)	75W	-	Use good grade oil of famous brand.
			-10 ~ 30°C (14 ~ 86°F)	80W	80W-90	
			0 ~ 35°C (32 ~ 95°F)	85W	85W- 140	
			10°C (50°F) & above	90		
Steering Gear Box.	Gear Oil	GL-3 or better	All seasons	80W ~ 90	80W-90 or 85W-140	Use good grade oil of famous brand. Not requiring periodical service. Replace only when overhauling.

* **NOTE:** As transmission oil is also used as hydraulic oil, gear oil with higher viscosity will give a very bad influence on starting behaviour of the engine. From this standpoint this kind oil is recommendable for the areas of very low air temperature in winter season.
For more details, please ask local dealer.