



Dimensions - Cab tractors (4320, 4520, 4720)

4020 Cab Tractor dimensions

4020 Cab Tractor dimensions

Tires (wheel position):	R1 Bar	R3 Turf	R4 Ind.	R3 Turf
Rear	13.6-28 (8-position)	44x18.00-20 (2-position)	17.5L-24 (2-position)	22.5LL-16.1 (2-position)
Front	8-16 (2-position)	27x10.5-15 (2-position)	10-16.5 (2-position)	27x12LL-15 (2-position)
Dimensions:				
(A)-Wheelbase, in. (m)	71.5 (1.8)	71.5 (1.8)	71.5 (1.8)	71.5 (1.8)
(B)-Overall length w/ 3-point hitch, in. (m)*	128.2 (3.3)	128.2 (3.3)	128.2 (3.3)	128.2(3.3)
(C)-Overall width (min.), in. (m)	65.6 (1.7)	74.0 (1.9)	68. (1.7)	81.4(2.1)
Overall width (max.), in. (m)	89.1 (2.3)	86.6 (2.2)	91.9 (2.4)	86.6 (2.2)
(D)-Inside width (min.), in. (m)	37.0 (0.9)	37.0 (0.9)	34.2 (0.8)	35.6 (0.9)
Inside width (max.), in. (m)	60.4 (1.5)	40.1 (1.2)	57.7 (1.5)	40.8 (1.0)
Height from ground:				
(E)-To top of hood, in. (m)	61.9 (1.4)	54 (1368)	56 (1424)	54 (1368)
(F)-To top of cab, in. (m)	95.4(2.42)	91.2(2.32)	93.8 (2.38)	91.4(2.32)
(G)-Ground clearance, rear axle, in. (mm)	14.6 (372)	11.7 (298)	14.6 (372)	10.6 (275)
Wheel treads (center-to-center in narrow position):				
(H)-Rear wheels, in. (mm)	51.3 (1304) position 2	55.2 (1408)	51.3 (1304)	58.6 (1487)
Front wheels, in. (mm)	55 (1385)	55 (1385)	53 (1349)	55 (1385)
Turning radius:				
With brakes, MFWD off, ft (m)	9.2 (2.8)	9.2 (2.8)	9.2 (2.8)	9.2 (2.8)
Without brakes, MFWD off, ft (m)	9.8 (3.0)	9.8 (3.0)	9.8 (3.0)	9.8 (3.0)