



**Dimensions - Open-station tractors (4120, 4320, 4520, 4720)**

4020 Open-Station Tractor dimensions

4020 Open-Station Tractor dimensions

Tires (wheel position):	R1 Bar	R3 Turf	R4 Ind.	R3 Turf
Rear	13.6-28 (8-position)	44x18.00-20 (2-position)	17.5L-24 (2-position)	22.5LL-16.1 (2-position)
Front	8-16 (2-position)	27x10.5-15 (2-position)	10-16.5 (2-position)	27x12LL-15 (2-position)
<b>Dimensions:</b>				
(A)-Wheelbase, in. (m)	71.5 (1.8)	71.5 (1.8)	71.5 (1.8)	71.5 (1.8)
(B)-Overall length w/ 3-point hitch, in. (m)*	128.2 (3.3)	128.2 (3.3)	128.2 (3.3)	128.2(3.3)
(C)-Overall width (min.), in. (m)	65.6 (1.7)	74.0 (1.9)	68.4 (1.7)	81.4 (2.1)
Overall width (max.), in. (m)	89.1 (2.3)	85.4 (2.2)	91.9 (2.4)	86.6 (2.2)
(D)-Inside width (min.), in. (m)	37.0 (0.9)	37.0 (0.9)	34.2 (0.8)	35.6 (0.9)
Inside width (max.), in. (m)	60.4 (1.5)	40.1 (1.2)	57.7 (1.5)	40.8 (1.0)
<b>Height from ground:</b>				
(E)-To top of hood, in. (m)	61.9 (1.4)	58.1 (1.5)	60.8 (1.5)	59.1 (1.5)
(F)-To top of folding ROPS, in. (m)	97.2 (2.5)	93.4 (2.4)	96.1 (2.4)	94.4 (2.4)
(G)-Ground clearance, drawbar support, in. (mm)	14.6 (372)	10.8 (275)	11.8 (300)	9.36 (238)
<b>Wheel treads (center-to-center in narrow position):</b>				
(H)-Rear wheels, in. (m)	54.6 (1.4) position 2	53.2 (1.4)	53.1 (1.4) position 2	53.2 (1.4)
Front wheels, in. (mm)	55 (1385)	55 (1385)	53 (1349)	55 (1385)
<b>Turning radius:</b>				
With brakes, 4WD off, ft (m)	9.2 (2.8)	9.2 (2.8)	9.2 (2.8)	9.2 (2.8)
Without brakes, 4WD off, ft (m)	9.8 (3.0)	9.8 (3.0)	9.8 (3.0)	9.8 (3.0)

\* Overall length is from 3-point hitch in level position to front bumper. Subtract 7.6 in. for tractors without 3-point hitch.