

L-Series

	L3200DT(2WD)/ DT(4WD)/HST(4WD)	L3800DT(2WD)/ DT(4WD)/HST(4WD)	L3700SU	L4400DT-1(4WD)/ HST-1(4WD)
Engine Type (Kubota, liquid-cooled, diesel)	E-TVCS, 3-cylinder	E-TVCS, 3-cylinder	E-TVCS, 3-cylinder	E-TVCS, 4-cylinder
Displacement (cu.in.)	91.5	111.4	111.4	134.1
Horsepower (gross)	31.9	37.4	37.4	45.3
Horsepower (PTO)	26.7/25.2	31.5/30.3	30.0	DT: 37.5/ HST-1: 36.0
Clutch	Dry-type single stage	Dry-type dual stage (F-1/DT-1) Dry-type single stage (HST-1)	Dry-type single stage	Dry-type single stage
Wheelbase (min. tread)	55.1"	55.1"	51.4"	62.4"
Wheelbase (2WD)	63.3"	63.3"	N/A	N/A
Wheelbase (4WD)	63.3"	63.3"	63.3"	72.6"
Ground Clearance	13.4" 4WD/ 13.6" 2WD	13.4" 4WD/ 13.6" 2WD	13.4"	15.7"
Speeds (mph) forward/reverse)	DT: 1-13.7/1.5-4.9 HST: 0-14.7/0-13.2	DT: 1.1-13.2/1.5-4.7 HST: 0-14.1/0-12.7	0-14.1/0-12.7	DT: 1/1.2-14.9/1.5-5.1 HST-1: 0-15.8/0-14.2

COMPATIBLE IMPLEMENTS

Backhoe	BH76/BH77	BH76/BH77	BH76/BH77	BH92
Front Loader	LA463FL/LA463-1/ LA524/FL	LA463FL/LA463-1/ LA524/FL	LA463FL/LA463-1	LA703A

BACKHOE SPECIFICATIONS

	BH76	BH92	BH77
Digging Depth (max.)	92.2"	110.9"	92.5"
Loading Height	64.4"	84.3"	66.7"
Bucket Sizes	10", 12", 16", 24"	12", 16", 18", 24", 30", 36"	10", 12", 16", 24"

FRONT LOADER SPECIFICATIONS

	LA463FL	LA463-1	LA524	LA524FL	LA703A
Maximum Lift Height Pivot Pin	95.3"	95.3"	94.3"	94.3"	102.4"
Lift Capacity-Full Height Pivot Pin (lbs.)	1142	1142	1490	1490	1818
Bucket Width	60.0"	66.0"	60.0"	66.0"	72.0"

ADDITIONAL IMPLEMENTS AND ACCESSORIES

	L3200 Models	L3800 Models	L3700SU	L4400 Models
Rear Mount Snowblower	64"	64"	64"	64", 74"