

SECTION 4 - SPECIFICATIONS

| | Model TC40DA | Model TC45DA |
|------------------------------------|---------------------|---------------------|
| WHEEL TREAD SETTINGS: | | |
| <i>FRONT AXLE:</i> | | |
| <i>Agricultural:</i> | | |
| FWD | 7 X 16 | 1179.0 mm (46.4 in) |
| | 8 X 16 | 1179.0 mm (46.4 in) |
| <i>Turf:</i> | | |
| FWD | 25 X 8.5-14 | 1264.9 mm (49.8 in) |
| | 27/12LL x 15 | 1368 mm (53.86 in) |
| <i>Industrial:</i> | | |
| 4WD | 10 X 16.5 | 1253 mm (49.3 in) |
| <i>REAR AXLE:</i> | | |
| - sm AG Tires 13.6 x 24 | 47.1 (1197) | 47.1 (1197) |
| - MIN (Dished In) | 67.4 (1712) | 67.4 (1712) |
| - MAX (Dished Out) | 6 | 6 |
| - No. of available positions | 4 (102) | 4 (102) |
| - Adj. per person | | |
| - lg AG Tires 14.9 x 24 | 47.5 | 47.5 |
| - MIN (Dished In) | 67.4 (1712) | 67.4 (1712) |
| - MAX (Dished Out) | 5 | 5 |
| - No. of available positions | 4 (102) | 4 (102) |
| - Adj. per person | | |
| - R4 Tires 17.5 x 24 | 51.2 (1301) | 51.2 (1301) |
| - MIN (Dished In) | 67.4 (1712) | 67.4 (1712) |
| - MAX (Dished Out) | 5 | 5 |
| - No. of available positions | 4 (102) | 4 (102) |
| - Adj. per person | | |
| - TURF Tires 44 x 18 - 20 | 53 (1347) | 53 (1347) |
| - MIN (Dished In) | 53.9 (1368) | 53.9 (1368) |
| - MAX (Dished Out) | | |
| - Only 2 available positions | | |
| 22.5LL x 16 | 1550 mm (61.03 in) | 1550 mm (61.03 in) |
| WEIGHT: | | |
| <i>With CAB:</i> | | |
| FWD | 1300 kg (2860 lb) | 1340 kg (2949 lb) |
| SuperSteer | 1377 kg (3029 lb) | 1417 kg (3118 lb) |

SECTION 4 - SPECIFICATIONS

| | Model TC40DA | Model TC45DA |
|--|---------------------|---------------------|
| (2) - WHEEL BASE: | | |
| FWD | 1866.9 mm (73.5 in) | 1866.9 mm (73.5 in) |
| SuperSteer | 2057.4 mm (81.0 in) | 2057.4 mm (81.0 in) |
| HEIGHTS - in (mm): | | |
| (3) - Steering Wheel Height | | |
| sm AG 4WD | Variable | Variable |
| lg AG 4WD | Variable | Variable |
| R4 4WD | Variable | Variable |
| TURF 4WD | Variable | Variable |
| (4) - Hood Height (top inst. cluster) | | |
| sm AG 4WD | 59 (1499) | 59 (1499) |
| lg AG 4WD | 59.5 (1511) | 59.5 (1511) |
| R4 4WD | 60 (1524) | 60 (1524) |
| TURF 4WD | 58 (1473) | 58 (1473) |
| (5) - WIDTH: | | |
| Rear Axle—Outside to Outside: | | |
| <u>Turf Tires—</u> | | |
| Dished In | 1823.7 mm (71.8 in) | 1823.7 mm (71.8 in) |
| Dished Out | 1846.6 mm (72.7 in) | 1846.6 mm (72.7 in) |
| <u>Ag. Tires— (Large)</u> | | |
| Dished In | 1691.6 mm (66.6 in) | 1691.6 mm (66.6 in) |
| Dished Out | 2103.1 mm (82.8 in) | 2103.1 mm (82.8 in) |
| <u>R4 Tires—</u> | | |
| Dished In | 1736 mm (68.3 in) | 1736 mm (68.3 in) |
| Dished Out | 2146 mm (84.5 in) | 2146 mm (84.5 in) |
| (6)—GROUND CLEARANCE: | | |
| sm AG TIRES | | |
| (D.) - Minimum Centerline Clearance | 13 (330) | 13 (330) |
| - Location (Super Steer Clutch) | 11 (279) | 11 (279) |
| (E.) - Frt Axle Crop Clear. - 15 in from CL .. | 15.5 (394) | 15.5 (394) |
| (F.) - Rr Axle Crop Clear. - 15 in from CL ... | 17.5 (445) | 17.5 (445) |
| lg AG TIRES | | |
| (D.) - Minimum Centerline Clearance | 14 (356) | 14 (356) |
| - Location (Super Steer Clutch) | 11 (279) | 11 (279) |
| (E.) - Frt Axle Crop Clear. - 15 in from CL .. | 15.5 (394) | 15.5 (394) |
| (F.) - Rr Axle Crop Clear. - 15 in from CL ... | 18 (457) | 18 (457) |
| R4 TIRES | | |
| (D.) - Minimum Centerline Clearance | 14 (356) | 14 (356) |
| - Location (Super Steer Clutch) | 11.5 (292) | 11.5 (292) |
| (E.) - Frt Axle Crop Clear. - 15 in from CL .. | 15.5 (394) | 15.5 (394) |
| (F.) - Rr Axle Crop Clear. - 15 in from CL ... | 17.5 (444) | 17.5 (444) |
| TURF TIRES | | |
| (D.) - Minimum Centerline Clearance | 11.5 (292) | 11.5 (292) |
| - Location (Super Steer Clutch) | 9 (229) | 9 (229) |
| (E.) - Frt Axle Crop Clear. - 15 in from CL .. | 13 (330) | 13 (330) |
| (F.) - Rr Axle Crop Clear. - 15 in from CL ... | 15 (381) | 15 (381) |

CL - Center Line of Tractor