








Specifications

Model					
Cylinders			3		
Bore x Stroke		mm(in.)	83(3.27)x92.4(3.64)	87(3.43)x92.4(3.64)	87(3.43)x102.4(4.03)
Displacement		L(cu.in.)	1.499(91.47)	1.647(100.5)	1.826(111.4)
Combustion / Intake system			E-TVCS,NA		
Cooling system			Liquid-Cooled		
Starter		V-kW	12-1.4	12-1.4	12-2.0
Speed		rpm	2800	2800	2600
Output	Gross intermittent	kW(HP)(PS)	24.9(33.4)(33.9)	27.4(36.7)(37.3)	28.4(38.1)(38.6)
	Net intermittent		23.5(31.5)(32.0)	25.7(34.5)(35.0)	26.9(36.0)(36.5)
	Net continuous		20.4(27.3)(27.7)	22.4(30.0)(30.4)	23.3(31.3)(31.7)
Dimensions	Length	mm(in.)	572.1(22.5)	572.1(22.5)	575.9(22.7)
	Width	mm(in.)	499.0(19.6)	499.0(19.6)	499.0(19.6)
	Height1	mm(in.)	643.0(25.3)	643.0(25.3)	684.0(26.9)
	Height2	mm(in.)	229.3(9.0)	229.3(9.0)	265.5(10.5)
Dry Weight		kg(lb)	148.0(326.3)	148.0(326.3)	151.0(332.9)

Model						
Cylinders			4			
Bore x Stroke		mm(in.)	83(3.27)x92.4(3.64)	87(3.43)x92.4(3.64)	87(3.43)x102.4(4.03)	83(3.27)x92.4(3.64)
Displacement		L(cu.in.)	1.999(121.98)	2.197(134.1)	2.434(148.5)	1.999(112.0)
Combustion / Intake system			E-TVCS,NA			E-TVCS,Turbo
Cooling system			Liquid-Cooled			
Starter		V-kW	12-1.4		12-2.0	12-1.4
Speed		rpm	2800	2800	2600	2800
Output	Gross intermittent	kW(HP)(PS)	33.2(44.5)(45.1)	36.4(48.8)(49.5)	38.0(51.0)(51.7)	44.0(59.0)(59.8)
	Net intermittent		31.6(42.4)(43.0)	34.3(46.0)(46.7)	35.8(48.0)(48.7)	41.8(55.3)(56.1)
	Net continuous		27.2(36.5)(37.0)	29.8(40.0)(40.5)	31.1(41.7)(42.3)	36.3(47.5)(48.2)
Dimensions	Length	mm(in.)	667.1(26.3)	667.1(26.3)	670.9(26.4)	667.1(26.3)
	Width	mm(in.)	499.0(19.6)	499.0(19.6)	499.0(19.6)	499.0(19.6)
	Height1	mm(in.)	634.5(25.0)	634.5(25.0)	684.0(26.7)	672.5(26.5)
	Height2	mm(in.)	221.0(8.7)	221.0(8.7)	265.5(10.5)	221.0(8.7)
Dry Weight		kg(lb)	180.0(396.9)	180.0(396.9)	184.0(405.7)	184.0(405.7)

*Specifications are subject to change without notice.

*Dry weight is according to Kubota's standard specifications.

*Gross Intermittent: 1-hour rating based on engine without cooling fan, air cleaner and muffler, with alternator (Idling). (SAE J1995)

*Net Intermittent: 1-hour rating based on engine with standard cooling fan, air cleaner, muffler, and alternator (Idling). (SAE J1346, ISO 3046 IFN)

*Net Continuous: Continuous rating based on engine with standard cooling fan, air cleaner, muffler, and alternator (Idling). (ISO 3046 IC15N)

*Atmospheric Condition: Ambient temperature 25 C. Relative humidity 30%, Barometric pressure 750 mm Hg (100 kPa)

*Conversion Formula: HP=0.746 kW, PS=0.7355 kW

*Height 1 : Overall Height

*Height 2 : From crankshaft center to lower edge of engine.