

FTX140



Track Carriers

**Big Power
Small Package**



Technical Specifications

GENERAL	FTX140
Weight of Tractor Only	12,700 lbs.
Weight with Stump Cutter	15,000 lbs.
Weight with Bull Hog® Mulcher	15,300 lbs.
Length of Tractor Only	148"
Height / Width	98"/73"
Ground Clearance	15."
Travel Speed (low/hi)	2.4 / 4.2 mph
Ground Pressure	5.4 psi
Truck Gauge	61"
ENGINE	
Model	John Deere Engine 4045H 140 HP
Number of Cylinders	4
Gross Power	2400RPM
Cooling	Liquid Cooled
Fuel Tank Capacity	60 Gallons
Fuel Consumption (average)	10 gal/h
Lift Cylinders	23" x 4" diameter
Roll Cylinder	3.5 diameter
Oil Filter	Spin-On Type
Air Cleaner	Dry Type Dual Element with Pre-Cleaner
HYDRAULIC SYSTEM	
System Pressure	6000 psi
High Flow	69 gpm
Low Flow	15 gpm
Hydraulic Reservoir	30 gallons

The most powerful hydraulic tractor in the compact equipment industry. FTX140-FM is configured as a tool carrier to run multiple attachments: Bull Hog Mulchers, Stump Hog, Dozer Blade, Rear Grapple

FEATURES

- BH85FM with hydraulic tilting push bar
- Hydraulic cooler and hydraulic reversing fan
- 69gpm/ 6000psi with load sense hydraulics.
- Pressurized cab with heat and A/C.
- Powerful tractive effort through single bar steel tracks
- Rear hydraulics

APPLICATIONS

- Land Clearing
- Forestry applications
- Orchard clean-up and removal
- Prairie and wetland restoration
- Agricultural preparation and land development
- Wild fire urban interface mechanical fuel treatments
- Mulch brush, branches, slash, standing and fallen trees, root balls, and stumps

ACCESSORIES

- **Standard Winch** - Excellent for pulling machines out of difficult situations, or skidding logs.
- **Skidder Winch** lifts logs higher in the air for easier skidding.
- **Ripper** - Designed to pre-rip tough soil or frozen ground.
- **Rear Grapple** - Moving debris, rock and brush piles. Log loading and unloading, skidding logs.
- **Bucket** - Scooping and carrying small material on hard surfaces, clearing debris, rocks and trees.
- **Front Grapple** - Transport/ placing landscape materials, tree removal and moving debris, rocks and brush piles.
- **Stump Grinder SH140** - Grind stumps up to 36" below ground.



Winch Options: (A) Skidder Winch (B) Standard Winch

- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Safety Is The Responsibility Of The Operator.
- Always insure that your carrier manufacturers safety features, including Falling Object Protection meet your job safety requirements.
- Specifications subject to change without notice.
- LEXAN® is a registered trademark of General Electric Company.



3460 Grant Drive
Lebanon, OH 45036
www.fecon.com
E-Mail: sales@fecon.com



Phone: 513.696.4430
Fax: 513.696.4431
Toll Free: 800.528.3113