



ROTARY MOWERS WITH I BEAM SIDES



The **Gearmore Rotary Mowers** are the strongest economical rotary mowers on the market today. Featuring the unique I beam sides insures strength where the deck needs it most. Some of the other special features include floating hitch that follows the contour of the terrain, heavy round spindle pan to protect the gearbox, two heavy full length tubes 1 1/2" x 2 1/2" for deck support, laminated tailwheel, all engineered to assure years of trouble free service.

FEATURES:

- Strong I beam sides to help prevent damage to mower deck
- External deck ribbing for added strength
- Internal deck angle iron brackets for additional support
- Heavy round dished spindle pan
- Reinforced a-frame with bracing to the rear of the mower
- Floating hitch design follows the contour of the terrain
- Forged heat treated blades and blade bolts

Side Plates: 6" I Beams w/Gussets
Front & Rear

Hitch: Cat. 1

Gearbox: 40 H.P.

Gearbox RPM: 540

Tailwheel: Laminated

Cutting Height: 1" to 10"

Blade Size: 1/2" x 3"

Blade Pin: 1 1/2" Diameter

Driveshaft: Shear Pin Protection
or Optional Slip Clutch

WARNING: If operating mower near roads and/or where people are present, you *must* equip mower with deck shielding.

SPECIFICATIONS:

MODEL NO:	LG40	LG48	LG60	LG72
Cutting Width:	40"	48"	60"	72"
Overall Width:	43"	51"	63"	75"
Overall Length:	72"	82"	95"	107"
Blade Tip Speed:	11,000	11,500	12,500	15,000
Deck Material:	12 Ga.	12 Ga.	12 Ga.	10 Ga.
Mower Weight:	390#	465#	590#	680#

