

ORDER CODE	DESCRIPTION	APPROX. SHIP WT.	SUGGESTED LIST PRICE
Rear Remote Hydraulics (B2630 / B3030)			
Must order Base Kit and one Valve Section to complete installation.			
B7306	Base Kit and 1 st Lever Requires B7304 Valve to complete Assembly (for 1 valve).	16	\$ 412.00
B7304	Double Acting Valve Section Requires: B7306 / B7307	15	\$ 206.00
B7305	Float Detent Valve Section (for 2nd position only) Requires: B7307	10	\$ 258.00
B7307	Second Position Stacking Kit for 2nd Valve Includes Hardware and 2 nd Lever Requires: Additional B7304 or B7305 Valve Section	10	\$ 206.00
Additional Valve Types, Dealer installed (Select a valve Section/s and the appropriate Stacking kit to complete)			
BL7343	Two Spool Stacking Kit Second Position to install dual valve Hardware and o-rings to install one (1) Additional valve section for B7333	20	\$ 25.00
BL7353	Three Spool Stacking Kit Third Position to install triple valve hardware and O-rings to install two (2) additional valve sections to BL7303 or B7333	25	\$ 29.00
BL7373	3-Position, DV-Detent Valve (Not Self-canceling) Closed Detent Valve Section The Valve Section features a single spool that should be used for double acting cylinders, both work ports are blocked in the neutral position with free flow oil through the valve in neutral. Important: The Detent position is not self-canceling and will not release when cylinder reaches end of stroke. Leaving this valve in Detent position on a blocked circuit will cause system relief valve to remain open.	20	\$ 223.00
BL7393	4-Position, FD- Float Detent Section Both work ports are blocked in the neutral position. The Detent "float" position allows the hydraulic cylinder to float. Both work ports are blocked in the neutral position with free flow oil through the valve in neutral.	25	\$ 254.00
B2056-1 ①②	Hydraulic Valve Kit for B1700, B2100, B2400, B7610, B2410, B7300, B7400, B7410, B7500, and B7510	30	\$ 617.00
B2099-1 ①②	Hydraulic Valve Kit for B2710 and B2910	58	\$ 617.00

① Valve Stand incorporates right side mid-mount mower bracket.

② Four position (dump) spool valve required for front mount implements, without Loader.