

## Loader Specifications

Model	LA203		LA243	
	BX1860			
Max. lift height (to bucket pivot pin)	mm	1810	1810	
Dumping clearance	mm	1350	1330	
Dumping reach at max. lift height	mm	720	735	
Max. dump angle	degrees	40	45	
Reach with bucket on ground	mm	1330	1390	
Bucket rollback angle	degrees	30	29	
Digging depth	mm	100	120	
Overall height in carrying position	mm	970	990	
Bucket width	mm	1230	1230	
Lift capacity (500mm fwd., max. height)	kg	185	235	
Lift capacity (pivot pin, max. height)	kg	278	338	
Breakout Force (500mm fwd.)	N	3920	4410	
Raising time to full height w/o load	second	2.8	3.5	
Lowering time w/o load	second	2	2.7	
Bucket rollback time	second	2.1	2.4	
Bucket dumping time	second	1.8	1.7	
Rated flow	Litres/min.	14	14	
Relief valve PSI	kg/cm <sup>2</sup> (psi)	125 (1778)	125 (1778)	
Lift cylinder bore diameter	mm	40	40	
Tilt cylinder bore diameter	mm	65	65	
Bucket capacity (struck)	m <sup>3</sup>	4.2	4.9	

## Mid-Mount Mower Specifications

Model	RCK54-23BX		RCK60B23BX	
	BX1860/BX2360/BX2660/BX25		BX2360/BX2660/BX25	
Type	Side discharge			
Number of blades	3			
Mounting method	Suspended-Linkage		Self Balance	
Cutting width	mm	1372	1524	
Cutting height	mm	25-102		
Adjustment of cutting height	Dial gauge			
Weight	kg	86	115	

*The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.*

### Industrial tyre

(BX25 only)

### Turf tyre

(BX1860, BX2360, BX2660 only)

### Bar tyre

(BX1860, BX2360, BX2660 only)

