



## Daedong-USA, Inc. Kioti Tractor Division

6300 Kioti Dr.

Wendell NC, 27591

Tel: (919) 374-5100

Toll Free: (877) GO-KIOTI

Fax: (919) 374-5001

Revised July 20, 2012

### FLUID/LUBRICANT CHART

Tractor	Engine Oil Capacity & Type (US Quarts)	Transmission Oil Capacity & Type (US Gallons)	Fuel Capacity & Type (US Gallons)	Front Axle Oil Capacity & Type (US Quarts)	Lubricating Grease Capacity & Type	Brake/Clutch Fluid Capacity & Type (US Fluid Ounces)
LB 1714	3.3	6.35	5	2.1	As Needed	N/A
LB 1914	3.3	6.35	5	2.1	As Needed	N/A
LK 2204	5.6	6.35	5.9	1.73	As Needed	N/A
LK 2552	5.5	7.4	7.4	2.6	As Needed	N/A
LK 2554	5.5	7.4	7.4	2.6	As Needed	N/A
LK 3054	6.76	6.86	7.4	6.32	As Needed	N/A
LK 30	6.12	6.86	7.4	4.76	As Needed	N/A
LK 3504	6.76	6.86	7.4	6.32	As Needed	N/A
CK 20 HST	2.76	4.89	5.28	3.3	As Needed	N/A
CK 20 Gear	2.76	5.71	5.28	3.3	As Needed	N/A
CK 20S HST	3.36	4.89	5.28	3.28	As Needed	N/A
CK 20S Gear	3.36	5.71	5.28	3.28	As Needed	N/A
CK 25 HST	6.12	7.93	7.9	4.8	As Needed	N/A
CK 25 Gear	6.12	7.13	7.9	4.8	As Needed	N/A
CK 30 HST	6.12	7.93	7.9	4.8	As Needed	N/A
CK 30 Gear	6.12	7.13	7.9	4.8	As Needed	N/A
CK 35 HST	6.12	7.93	7.9	4.8	As Needed	N/A
CK 35 Gear	6.12	7.13	7.9	4.8	As Needed	N/A
DS3510	6.12	6.86	7.9	4.8	As Needed	N/A
DS4110/DS4110HS	8.44	13.74	11.9	7.92	As Needed	N/A
DS4510/DS4510HS	8.44	13.74	11.9	7.92	As Needed	N/A
DK 35	6.1	11.62	10.6	7.9	As Needed	N/A
DK 35SE HST	6	11.1	11.9	7.6	As Needed	N/A
DK 35SE Gear	6	13.7	11.9	7.6	As Needed	N/A
DK 40	7.4	11.6	8.98	8.6	As Needed	N/A
DK 40SE HST	8.4	11.1	11.9	7.6	As Needed	N/A
DK 40SE Gear	8.4	13.7	11.9	7.6	As Needed	N/A
DK 45	7.6	9	10.6	8.8	As Needed	N/A
DK 45S	7.6	10	15.3	8.8	As Needed	N/A
DK 45SE HST	8.4	11.1	11.9	7.6	As Needed	N/A
DK 45SE Gear	8.4	13.74	11.9	7.92	As Needed	N/A
DK 50	7.6	9	10.6	8.8	As Needed	N/A
DK 55	8.8	10	18	8.8	As Needed	N/A
DK 65	6.8	15.3	26.4	12.56	As Needed	16 oz. Brake only
DK 65S	7.2	15.3	26.4	12.56	As Needed	18 oz. Brake & Clutch share a common reservoir
DK75	11	15.85	26.4	12.56	As Needed	16oz.Brake Only
DK90	11	19.5	33	12.15	As Needed	16 oz. Brake only
RX6010	9.2	15.3	25.1	8.8	As Needed	N/A
Mechron 2200	3.4	0.96 (HYD DUMP 15.88)	7.39	Front 0.52/ Rear 0.8	As Needed	DOT 3 As Needed
CS2410	4.4	13.6	7.1	2	As Needed	N/A
Multi-grade motor oil based on expected ambient temperatures between oil change intervals. Choose an oil with an SAE rating of CC, CD or higher. Below 32°F - SAE 10W-30 Above 32°F - SAE 15W-40		Multi-grade transmission fluid rated for differentials, final drives, wet brakes, and hydraulic systems enclosed in a common reservoir.	No. 2 Diesel Use No. 1 Diesel below 15°F or an acceptable anti-gel additive.	SAE 80W-90 gear oil or transmission fluid.	Multi Purpose	Anti-wear Hydraulic Fluid ISO Viscosity Grade 32 Example: Shell Tellus 32
<b>Potential Engine Oil Supplier, Name, and Weight</b> Valvoline Premium Blue 15W-40 Chevron Delo 400 15W-40 Castrol Tecton HD 10W-30, 15W-40 Texaco URSA Super Plus 10W-30, 15W-40 Pennzoil Long Life HD 10W-30, 15W-40 Mobil Delvac 1300 Super 10W-30, 15W-40 Exxon XD-3 10W-30, 15W-40 Quaker State Universal HDX 10W-30, 15W-40 Shell Rotella 10W-30, 15W-40	<b>Potential Transmission Oil Supplier and Name</b> Texaco TDH Oil Exxon Hydraul 560 Exxon Torque Fluid 56 Pennzoil Hydra Tranz Mobilfluid 424 BP TracTran UTH Shell Donax TD Citgo Mystik JT-5 Universal	* For additional assistance, please consult with your local Kioti Dealer. *				