



Figure 61

- | | | | |
|---|------------------------------|---|----------------------------------|
| A | Maximum lift height | G | Digging depth |
| B | Clearance with bucket dumped | H | Overall height in carry position |
| C | Reach at maximum height | L | Length of bucket |
| D | Maximum dump angle | R | Rollback angle at full height |
| E | Reach with bucket on ground | W | Lift capacity to full height |
| F | Bucket rollback angle | | |

	1120/1215/1220	TC18	TC21/21D
A	1978 mm (77.9")	1978 mm (77.9")	1978 mm (77.9")
B	1581 mm (62.3")	1581 mm (62.3")	1581 mm (62.3")
C	420 mm (18.5")	420 mm (18.5")	420 mm (18.5")
D	40°	40°	40°
E	1264 mm (49.8")	1264 mm (49.8")	1264 mm (49.8")
F	18°	18°	18°
G	121 mm (4.75")	121 mm (4.75")	121 mm (4.75")
H	1181 mm (46.5")	1181 mm (46.5")	1181 mm (46.5")
L	460 mm (18.1")	460 mm (18.1")	460 mm (18.1")
R	117°	117°	117°
W*	272 kg (600 lbs.)	272 kg (600 lbs.)	272 kg (600 lbs.)

*Per ASAE 5301.2 Front End Agricultural Loader Rating