

SPECIFICATIONS OF THE TRACTOR

SPECIFICATION TABLE

Model			B26
			4WD
PTO power		kW (HP)	14.5 (19.5)*
Engine	Maker		KUBOTA
	Model		D1105-E2-D21
	Type		Indirect Injection. Vertical, water-cooled 4 cycle diesel
	Number of cylinders		3
	Bore and stroke		mm (in.) $\phi 78 \times 78.4$ ($\phi 3.1 \times 3.1$)
	Total displacement		cm ³ (cu.in.) 1123 (68.5)
	Engine gross power		kW (HP) 19.4 (26.0)*
	Rated revolution		rpm 2800
	Maximum torque		N-m (ft-lbs.) 77.6 (57.2)
	Battery		12 V, RC : 79 min, CCA : 433 A
Fuel		Diesel fuel No.1 [below-10°C(14°F)], Diesel fuel No.2 [above-10°C(14°F)]	
Capacities	Fuel tank	L (U.S.gals.)	31 (8.1)
	Engine crankcase (with filter)	L (U.S.qts.)	3.0 (3.2)
	Engine coolant	L (U.S.qts.)	4.5 (4.7)
	Transmission case (with oil tank)	L (U.S.gals.)	26 (6.9)
Dimensions	Overall length (without 3P)		mm (in.) 2557 (100.7)
	Overall width (min. tread)		mm (in.) 1365 (53.7)
	Overall height (with canopy)		mm (in.) 2273 (89.5)
	Wheel base		mm (in.) 1581 (62.2)
	Minimum ground clearance		mm (in.) 350 (13.8)
	Tread	Front	mm (in.)
Rear		mm (in.)	1050 (41.3)
Weight (with ROPS & FOPS, main frame)		kg (lbs.)	1182 (2606)
Clutch			N/A
Traveling system	Tires	Front	23 x 8.50-14
		Rear	12.4-16
	Steering		Hydrostatic type power steering
	Transmission		Main-hydrostatic transmission, 3 range gear shift (3 forward, 3 reverse)
	Brake		Wet disk type
Minimum turning radius (without brake)		m (feet)	2.5 (8.2)