

Model				B26	
				4WD	
Hydraulic unit	Hydraulic control system			Position control	
	Pump capacity	L / min (gals / min)		3P: 26.3 (7.0) Power steering: 16.0 (4.2)	
	Three point hitch			SAE Category 1	
	Max. lift force	At lift points	kg (lbs.)		970 (2139)
24 in. behind lift point		kg (lbs.)		760 (1676)	
PTO	Rear-PTO			SAE 1-3/8, 6 splines	
	PTO / Engine speed		rpm	1 speed 540 / 2768	

NOTE: * Manufacturer's estimate The company reserves the right to change the specifications without notice.

TRAVELING SPEEDS

(At rated engine rpm)

Model		B26			
Tire size (Rear)		12.4 - 16 R4 IND		12.4 - 16 Farm	
	Range gear shift lever	km / h	mph	km / h	mph
Forward	Low	0 to 4.5	0 to 2.8	0 to 4.8	0 to 3.0
	Middle	0 to 8.4	0 to 5.2	0 to 8.9	0 to 5.5
	High	0 to 17.8	0 to 11.1	0 to 18.6	0 to 11.5
Reverse	Low	0 to 4.0	0 to 2.5	0 to 4.2	0 to 2.6
	Middle	0 to 7.4	0 to 4.6	0 to 7.9	0 to 4.9
	High	0 to 15.8	0 to 9.8	0 to 16.5	0 to 10.3

Model		B26	
Tire size (Rear)		13.6 - 16 Turf	
	Range gear shift lever	km / h	mph
Forward	Low	0 to 4.9	0 to 3.1
	Middle	0 to 9.1	0 to 5.7
	High	0 to 19.0	0 to 11.8
Reverse	Low	0 to 4.3	0 to 2.7
	Middle	0 to 8.1	0 to 5.0
	High	0 to 16.9	0 to 10.5

The company reserves the right to change the specification without notice.