

# SPECIFICATIONS OF THE LOADER

## LOADER SPECIFICATIONS

LOADER MODEL		<b>TL500</b>
TRACTOR MODEL		B26
BOOM CYLINDER	BORE mm (in.)	50 (1.97)
	STROKE mm (in.)	399 (15.7)
BUCKET CYLINDER	BORE mm (in.)	55 (2.17)
	STROKE mm (in.)	382.5 (15.1)
CONTROL VALVE		One Detent Float Position, Power Beyond Circuit
MAXIMUM PRESSURE	MPa (kg/cm <sup>2</sup> , psi)	16.6 (169, 2402)
NET WEIGHT (APPROXIMATE)	kg (lbs.)	285 (628)

## BUCKET SPECIFICATIONS

LOADER MODEL		<b>TL500</b>	
MODEL		HD ROUND 60	LM ROUND 66
TYPE		QUICK ATTACH	
WIDTH	mm (in.)	1524 (60)	1676 (66)
DEPTH (L)	mm (in.)	453 (17.8)	623 (24.5)
HEIGHT (M)	mm (in.)	584 (23.0)	584 (23.0)
LENGTH (N)	mm (in.)	646 (25.4)	816 (32.1)
CAPACITY	STRUCK m <sup>3</sup> (CU.FT.)	0.22 (7.8)	0.32 (11.3)
	HEAPED m <sup>3</sup> (CU.FT.)	0.27 (9.5)	0.39 (13.8)
WEIGHT	kg (lbs.)	126 (278)	149 (328)