

GENERAL SPECIFICATIONS									
MODELS	E48-200	E54-200	E60-200	E66-220	E72-220	E78-240	E86-260	E94-260	E80-260INV
Recommended horsepower (HP)	16 @ 25	16 @ 25	16 @ 25	25 @ 40	25 @ 40	35 @ 50	40 @ 75	40 @ 75	40 @ 75
Cutting width	48"	54"	60"	66"	72"	78"	86"	94"	80"
Cutting height	26"	26"	26"	27 1/2"	27 1/2"	27 1/2"	33 1/2"	33 1/2"	33 1/2"
Impeller RPM	540	540	540	540	540	540	540	540	540
Impeller diameter	20"	20"	20"	22"	22"	24"	26"	26"	26"
Impeller shaft diameter	1"	1"	1"	1 1/4"	1 1/4"	1 9/16	1 9/16"	1 9/16	1 9/16
Impeller depth	7"	7"	7"	8"	8"	8 1/2"	11"	11"	11"
Impeller center height	13 1/2"	13 1/2"	13 1/2"	14 1/2"	14 1/2"	15 1/2"	17 1/4"	17 1/4"	17 1/4"
Balanced impeller	Std	Std	Std	Std	Std	Std	Std	Std	Std
Main auger diameter	17"	17"	17"	17"	17"	17"	20"	20"	20"
Balanced auger	Std	Std	Std	Std	Std	Std	Std	Std	-
Chute rotation on polyethylene	Manual	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	-
	Hydraulic cylinder	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	-
	Cylinder dimensions	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2 1/2" x 8"
	Closed cylinder length	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"
Manual deflector	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hydraulic deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Chute 1 or 2 deflectors	Std	Std	Std	Std	Std	Std	Std	Std	2
Carbon steel blade	Std	Std	Std	Std	Std	Std	Std	Std	Std
Adjustable skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
P.T.O shaft number	2	2	2	4	4	4	6	6	6
Driving chain number	50	50	50	60	60	60	60	60	60
Number of safety bolts	2	2	2	2	2	2	2	2	2
Hitch category	1	1	1	1	1	1	2	2	2
Approx. weight (lbs)	420	455	470	525	540	640	915	940	980

Weight of Econor snowblowers includes weight of the chute but not the accessories. Prices and specifications are subject to change without notice.